



# Total Access 600R

## Carrier Class Access Router for Small and Medium Enterprises

### Product Features

- Integrated T1/FT1 CSU/DSU
- Carrier-class durable housing
- Easy to navigate menu system
- Downloadable configuration files
- Frame Relay and PPP support
- Network Address Translation (NAT)
- Packet filtering
- DHCP server
- SNMP management
- Standard 10-year warranty

The Total Access® 600R is a cost-effective T1/FT1 access router designed for small and medium businesses, branch offices and campuses. The ADTRAN® Total Access 600R provides 1.54 Mbps for “always-on” Internet access or remote office connectivity. With its integrated CSU/DSU, the Total Access 600R provides Wide Area Network (WAN) access over a standard T1 or fractional T1 circuit.

With the Total Access 600R, carriers and enterprises can give multiple users network access over a single T1 connection. For simultaneous access to both a corporate network and the public Internet, the Total Access 600R offers the ability to configure multiple frame relay PVCs. In addition, the Total Access 600R includes NAT/NAPT and IP filtering which provides security from unauthorized access to the user’s network.

The Total Access 600R also provides a cost-effective campus connectivity solution. When used with private dry copper, the Total Access 600R delivers up to 1.54 Mbps to cross-campus network elements. This solution is ideal for extending Local Area Network (LAN) segments to other buildings.

The Total Access 600R allows users to quickly setup and easily manage their network. The Total Access 600R offers a DHCP server allowing devices on the LAN to obtain their IP addresses automatically. Additional network management features include access list and password protected Telnet sessions and Simple Network Management Protocol (SNMP) support. The Total Access 600R also contains ping and Telnet utilities for network troubleshooting.

With support for Trivial File Transfer Protocol (TFTP), the Total Access 600R makes configuration, installation and software upgrades simple. Software can be upgraded remotely using TFTP or locally using the craft interface. Setup and installation of the Total Access 600R is made simple through the use of configuration files that can be uploaded to the unit using TFTP or XModem.

The Total Access 600R provides the user with the most cost-effective way to access the public Internet and connect branch offices together. Additionally, it is backed by an industry-leading 10-year warranty and ADTRAN’s best-in-class 24-hour technical support.



**ADTRAN, Inc.**

Attn: Enterprise Networks  
901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963-8000  
256 963-8699 fax

**General Information**

800 9ADTRAN  
info@adtran.com  
www.adtran.com

**Pre-Sales**

**Technical Support**

800 615-1176 toll-free  
application.engineer@adtran.com  
www.adtran.com/support

**Where to Buy**

877 280-8416 toll-free  
channel.sales@adtran.com  
www.adtran.com/where2buy

**Post-Sales**

**Technical Support**

888 423-8726  
support@adtran.com  
www.adtran.com/support

**ACES Installation & Maintenance Service**

888 874-ACES  
aces@adtran.com  
www.adtran.com/support

**Global Inquiries**

256 963 8000 voice  
256 963-6300 fax  
international@adtran.com  
www.adtran.com/global

**For the regional office nearest you, visit:**

www.adtran.com/where2buy



TL19.1270



ADTRAN is an ISO 9001, ISO 14001, and a TL 9000 certified supplier.

64200600L1-8D June 2009  
Copyright © 2009 ADTRAN, Inc.  
All rights reserved.

# Total Access 600R



## Carrier Class Access Router for Small and Medium Enterprises

### Product Specifications

#### WAN Interface

- Integrated T1/FT1 CSU/DSU
- Line Rate: 1.544 Mbps +/- 75 bps
- Physical Interface: RJ-48C (Modular, 8-pin)
- Framing: D4 (SF)/ESF
- Line Code: AMI / B8ZS
- Input Signal: 0 to -36 dB
- DS0 Assignment: User selectable
- Timing: Loop and local

#### LAN Interface

- 10/100BaseT Ethernet
- Half or full duplex
- RJ-45
- Secondary IP address
- DHCP server
- IEEE 802.3

#### Protocol Support

- IP
- 802.1d Bridging (all protocols)
- DNS
- TCP
- RIP V1, V2 and static routes
- UDP, UDP Relay
- ICMP
- ARP
- PPP and Frame Relay

#### Frame Relay

- Support for both point-to-point and point-to-multipoint networks using up to 10 PVCs
- RFC 1490 Encapsulation (Multiprotocol Over Frame Relay)
- LMI types: LMI, ANSI (Annex D), CCITT (Annex A) and Static

#### PPP

- LCP, IPCP, BCP, CCP
- Van Jacobson (VJ) header compression

#### Security

- PAP, CHAP, EAP and Radius
- NAT/NAPT
- Packet Filtering by source and destination IP address, source and destination port number, MAC address, protocol or pattern

- Multi-layer password protection
- Telnet security: Access list and password protection

#### Management and Configuration

- Remote configuration via Telnet
- RS-232 Craft interface for local configuration (RJ-48C)
- LAN and WAN status LEDs
- Text-based configuration file support
- SNMP V2: RFC 1406, 1213, 1315
- Syslog client
- Software upgrade via Trivial File Transfer Protocol (TFTP) or XModem
- ICMP Ping utility

#### WAN Testing and Troubleshooting

##### Local Loopbacks

- Line and payload

##### Remote Loopbacks

- Line and payload
- CSU loopback

##### Error Counts

- ES, SES, SEF, FS, LCV, SLP and UAS
- **Alarm Status:** Loss of signal, red alarm, yellow alarm, blue alarm

#### Environmental

- Operating Temperature: 0° to 50°C, (30° to 113°F)
- Storage Temperature: -20° to 70°C, (-4° to 158°F)
- Relative Humidity: Up to 95% non-condensing

#### Physical

- Dimensions: 2" H x 7.5" D x 11.25" W
- Weight: 2 lbs.
- Agency approvals: UL1950, CUL, FCC Part 15 (Class A)
- AC Power: 90-130 VAC, 60Hz

### Ordering Information

Equipment	Part #
Total Access 600R T1 TDM	4203600L1#TDM
Total Access 600R T1 TDM w/DSX-1	4213600L1#TDM
Total Access 600R T1 ATM	4203600L1#ATM
Total Access 600R T1 ATM w/ DSX-1	4213600L1#ATM
Total Access 600R SHDSL	4203600L5
Total Access 600R SHDSL w/ DSX-1	4213600L5

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. and its affiliates in the U.S. and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. Five-year warranty applies only to products sold in North America.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense)