



M13 Multiplexer

MX2800 M13 Multiplexer

Product Features

- Affordable DS3 bandwidth consolidation
- Built-in 1:1 redundancy
- SNMP and Telnet management
- Temperature hardened
- Backhauls multiple service types (T1/E1)
- Smallest M13 form factor available
- Optional integrated V.34 modem and dial-out "cry for help"
- Dual redundant load sharing AC or DC power supplies available
- M13 and C-Bit signaling
- Industry-standard CSU and NIU loopback codes
- Advanced diagnostics including built-in BERT capability
- Software upgradable via modem or TFTP
- Full configuration and management from Total Access EMS
- NEBS Level 3 compliant
- Optional fan faceplate
- STS-1 version available
- Industry-leading, 10-year warranty

M13 remains an important part of network operations. Carriers need M13 elements that are reliable, cost effective, and conserve space. ADTRAN™ has applied its industry-leading carrier-class expertise to the MX2800™ M13 multiplexer, creating a product that meets the most stringent carrier-class requirements. The MX2800 offers bandwidth consolidation at a low price and in the smallest footprint available in the industry. The equipment meets stringent NEBS Level 3 requirements and is backed by a 10-year warranty. Measuring only one rack unit high in 19-inch or 23-inch rackmount configurations, this compact device gives NSPs and enterprise users a powerful tool for consolidating 28 T1 signals or 21 E1 signals into a T3 circuit. The MX2800 is also available in an STS-1 version.

The MX2800 houses two hot-swappable controller cards that are capable of combining independent T1s, E1s, or T1s and E1s, on the same DS3. The two controller cards also provide built-in 1:1 redundancy for the DS1 and DS3 signals as well as redundant DS3 connections. Advanced diagnostics include CSU loopbacks, NIU loopbacks, C-bit loopbacks and built-in BERT (Bit Error Rate Testing) capabilities. A fully connectorized backplane means no wire wrapping and quick, easy installation. Accessories available for the MX2800 include a DS1 patch panel that breaks out the 28 DS1s into 28 individual RJ-48 interfaces and a battery backup system that provides eight hours of battery backup.

As with all ADTRAN products, the MX2800 offers comprehensive management options, including full management and GUI support from ADTRAN's Total Access® EMS. It features a VT100 terminal interface for local configuration. To support SNMP and Telnet management, the MX2800 has an integrated 10Base-T Ethernet port. Also available is an optional integrated V.34 modem operable in VT100 mode or SLIP/PPP mode for SNMP and Telnet access. The modem is capable of performing a dial-out "cry for help" for units that are located in unmanned facilities.

Carriers who want to maximize their copper investment and consolidate services in the most efficient manner will find that the MX2800 will pay off quickly. For example, a bandwidth reseller who is co-located at an unmanned site and backhauling local and long distance voice service can use the MX2800 to gain T1 access off Hi-Cap SONET rings. The MX2800 is also ideal for Competitive Local Exchange Carriers (CLECs) who are also looking for an efficient means for backhauling local and long distance voice to or from the IXC or LEC. As Internet use continues its rapid expansion, Internet Service Providers are also well served with the MX2800's bandwidth consolidation.



ADTRAN, Inc.

901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963 8000 voice
256 963 8030 fax
877 457 5007 fax back

General Information

800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

888 5ADTRAN
support@adtran.com
www.adtran.com/support

Where to Buy

800 827 0807
www.adtran.com/where2buy

Post-Sales

Technical Support

800 726 8663
support@adtran.com
www.adtran.com/support

Regional Offices

Dallas, TX
972 830 9070
Denver, CO
303 471 9150
Irvine, CA
949 260 3500
Kansas City, KS
800 471 8649
Newark, NJ
800 471 8656
Ontario, Canada
416 290 0585
Quebec, Canada
877 923 8726
San Antonio, TX
888 223 7671

International Inquiries

+1 256 963 8716 voice
+1 256 963 6300 fax
international@adtran.com
www.adtran.com/international



ADTRAN is an
ISO 9001:2000 registered company.



ADTRAN is a
TL 9000 registered company.

M13 Multiplexer

MX2800 M13 Multiplexer

Product Specifications

Interfaces

T3 Network Interface

- Channelized DS3
- **Line build out:** Short (0 to 50 feet) and Normal (50 to 450 feet)
- **Framing format:** M13 and C-bit parity
- **Line rate:** 44.736 Mbps
- **Line interface:** Dual 75 ohm BNC coax female connectors

DSX-1 Interface(s)

- **Line build out:** 0 to 655 feet
- **Line rate:** 1.544 Mbps
- **Line code:** AMI or B8ZS
- **Line interface(s):** Dual 64 pin amp connectors

Diagnostics

DS3 Network

- ANSI T1.107 compatible loopbacks
- Line loopbacks

DSX-1 Ports

- Local and network loopbacks
- CSU and NIU loopbacks

Performance Monitoring

Local Network Port Statistics

Current 15 minute, 24 hour (96 15-minute intervals), total for 24 hours and cumulative

- Severely errored framing seconds
- Unavailable seconds
- Line coding violations
- Line errored seconds
- Far end block errors
- F-bit and M-bit errors
- P-bit errored seconds
- P-bit severely errored seconds
- P-bit coding violations
- C-bit coding violations
- C-bit errored seconds
- C-bit severely errored seconds

DSX Ports

- BPV
- LOS
- AIS (loop and carrier)

Mechanical

- **Dimensions:** 1.7 in. H X 7.86 in. D X 17 in. W
- **Weight:** 5.5 lb (fully redundant)



Specifications are subject to change without notice. ADTRAN and MX2800 are trademarks and Total Access is a registered trademark of ADTRAN, Inc. All other registered trademarks and trademarks mentioned in this publication are the property of their respective owners.

Clocking

- **Network:** Receive from DS3 network
- **Local:** Internally generated

Alarms

- External alarm contacts for critical and non-critical alarms
- Normally open and normally closed pinout
- Front panel alarm cutoff switch

Electrical

- **Power:** 120 VAC, 24 VDC or 48 VDC, 27 W

Regulatory Standards

- NEBS Level 3
- NRTL Safety Listed

Management

VT100 Terminal Interface

- RJ-48, EIA-232 compatible, female DB-9 adapter provided

Integrated Modem Interface (Optional)

- Dial up access for VT100, SNMP, or Telnet
- Dial out "cry for help"

SNMP/Telnet

- Integrated 10Base-T Ethernet
- MIB II, RFC 1213 and 1407 compliant
- ADTRAN Enterprise MIB for extended monitoring and control/configuration

Environmental

- Operating temperature: -40°C to 65°C
- Storage temperature: -20°C to 70°C
- Relative humidity: Up to 95 percent, noncondensing

Product Includes

- (1) 8-pin to 8-pin modular cable, (1) modular to female DB-9 adapter and user manual, mounting ears for 19-in. and 23-in. racks

Ordering Information

| Equipment | Part # |
|----------------------------------|-----------|
| MX2800 – AC with modem | 4205290L1 |
| MX2800 – AC Redundant with modem | 4205290L2 |
| MX2800 – DC with modem | 4205290L3 |
| MX2800 – DC Redundant with modem | 4205290L4 |
| MX2800 – AC | 4205290L5 |
| MX2800 – AC Redundant | 4205290L6 |
| MX2800 – DC | 4205290L7 |
| MX2800 – DC Redundant | 4205290L8 |
| RJ DSX-1 Patch Panel | 1200291L1 |

STS-1 and Fan versions also available