



IP Multi-service Access Node

hiX 5622

Product Features

- True IP multi-service access node
- Advanced service delivery - IPTV, POTS, ISDN, Business & Residential Ethernet, xDSL
- Carrier grade gateway between provider network and service subscriber
- Up to 108 Gbit/s Switching Capacity
- 2 Service slots
- Identical service cards for all shelf-based hiX 5600
- Copper and fibre transport and access
- Very high density for POTS and DSL access (up to 144 ports per shelf)
- Redundant (uplink, Power)
- Digital and metallic onboard test for voice and xDSL
- Supported by ACI-E EMS
- Temperature hardened (can be deployed in outside plant)
- Cabinet solutions available

The hiX 5622 is a high performance, carrier class IP multi-service access and aggregation node designed to ETSI standards. It bridges the gap between the carrier IP network and the end subscriber for POTS, ISDN, VDSL, SHDSL, ADSL, Fast Ethernet, GbE, IPTV and other services.

The hiX 5622 is built upon a pure IP core and supports both legacy and emerging service interfaces over copper and fibre. This mix of services on one platform enables service providers to future proof their networks. New services can be deployed with the simple change of a line card, equipment obsolescence can be avoided and network investments protected.

The chassis supports two service slots enabling the system to deliver up to 144 ports making it ideal for small to mid-size applications at the Central Office or deep in the network. Service slots include ADSL2+ (72 ports/slot), POTS (VoIP capable, 72 ports/slot), VDSL2 (48 ports/slot), ISDN (32 ports/slot), GbE (10 ports/slot), Fast Ethernet (48 ports/slot) and more. With the 10 GB capable star backplane architecture, the hiX 5622 provides high capacity and high reliability in one system. This is complemented by fully redundant 1 GbE or 10GE uplinks on central control card and redundant power supplies making the hiX 5622 truly carrier grade.

The system provides voice and data services as well as a simple migration path from legacy interfaces to IP. Voice services can be transitioned from POTS or ISDN to VoIP for example. Broadband data access can be provided using SHDSL, ADSL or VDSL (with or without splitters) as well as high density fibre using Fast Ethernet or Gigabit Ethernet. This unique mix of services from one single IP based platform enables service providers to quickly adapt to new business opportunities and remain highly competitive.

In order to ensure maximum flexibility, the common equipment and line cards are temperature hardened allowing the system to be deployed virtually anywhere, ranging from the Central Office to compact outdoor cabinets.

The hiX 5622 is managed by ADTRAN's Access Integrator Ethernet (ACI-E) Element Management System. The ACI-E EMS and hiX 5622 nodes communicate using SNMP via in-band or out-band channels. The ACI-E provides a Graphical User Interface (GUI) and northbound interfaces such as SNMP, TMF CORBA, WSPI (Web service based XML provisioning I/F) for a smooth integration into service provider operational systems.

ADTRAN, Inc.
International Department
U.S. Headquarters
 901 Explorer Boulevard
 Huntsville, Alabama 35806
www.adtran.com
 +1 256 963 8000
 +1 256 963 6300 fax
international@adtran.com

International Customer Service
 +1 256 963 8716

Asia—Beijing, China
 +86 10 8527 5011
 +86 10 8527 5010 fax
sales.china@adtran.com

Asia—Hong Kong
 +852 3187 7111
 +852 2116 4084 fax
sales.asia@adtran.com

Asia—Bangkok, Thailand
 +66 2 610 3724
 +66 2 610 3601 fax
sales.asia@adtran.com

Asia—Singapore
 +65 6232 2305
 +65 6232 2888 fax
sales.asia@adtran.com

**Australia/New Zealand—
 Melbourne, Australia**
 +61 3 9658 0500
 +61 3 9658 0599 fax
sales.australia@adtran.com

**Australia/New Zealand—
 Sydney, Australia**
 +61 2 8456 0101
 +61 2 8456 0105
sales.australia@adtran.com

**Canada Headquarters—
 Toronto, Ontario**
 +1 877 923 8726
 +1 514 989 3198 fax
 +1 905 625 2515
 +1 905 625 2511 fax
sales.canada@adtran.com

Canada—Montreal, Quebec
 +1 877 923 8726
 +1 514 940 2888
 +1 514 989 3198 fax
sales.canada@adtran.com

**European Regional
 Headquarters—United Kingdom**
 +44 (0) 1189 317080
sales.europe@adtran.com

**MEA Headquarters—
 Middle East and Africa**
 +971 2622 8007
 +971 2622 8024 fax
sales.mea@adtran.com


Mexico and Central America
 +1 256 963 3321 U.S.
 +1 52 55 4525 1633 Mexico
sales.mexico@adtran.com

Caribbean and Latin America
 +1 256 963 4177 U.S.
sales.cala@adtran.com
 +1 256 963 4177 U.S.
sales.caribbean@adtran.com

+1 256 963 9185 U.S.
 +1 55 19 2512 0661 Brazil
sales.brazil@adtran.com

IP Multi-service Access Node

hiX 5622



Product Specifications

Physical

Including cables and adapters

G200 2G: (21")

- **Dimensions:** 124 mm H, 533 mm W, 331 mm D

G200S 2G (19")

- **Dimensions:** 124 mm H, 482 mm W, 331 mm D

Interfaces

- **Maximum number of slots:** 4
- 2 x service-units, 1 x central units
- 1 x power module (1/2 slot size),
- 1 x power module (optional for redundancy)

Electrical

- DC Power: -40,5 to -72VDC
- Power connector: 3W3 male
- Power consumption maximum: 325 W

Regulatory Standards

- ETSI EN 300 019
- ETS 300 753
- DTAG TS 0364/96
- ETSI EN 300 386
- DTAG 1TR9
- ETS ES 201 468
- ETSI EN 60950
- ITU-T K.20/21/27/31/35/45

Environmental

- **Operating temperature indoor:** -25°C to +55°C
- **Operating temperature outdoor shelter:** -25°C to +70°C
- **Storage:** -45°C to +45°C
- **Transport:** -40°C to +70°C
- **Relative Humidity:** up to 100%, non-condensing

Ordering Information

Equipment	Part #
hiX 5622 Chassis 21" ETSI (G200 2G)	S50028-B3180-A1
hiX fan unit large w/o dust filter (<70°C)	S50028-B3181-A1
hiX fan unit large w/dust filter (<45°C)	S50028-B3181-A2
hiX filter pad for G200 2G w/dust filter	C50165-A230-C866
hiX 5622 chassis 19" (G200S 2G)	S50028-B3190-A1
hiX fan unit large w/o dust filter (<60°C)	S50028-B3191-A1

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN is a registered trademark of ADTRAN, Inc. and its affiliates in the U.S. and certain other countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit www.adtran.com/exportlicense