



Fiber Manager

Total Access 5000 Fiber Manager

The ADTRAN® Total Access® 22-Slot Expanded Fiber Manager enables the Carrier to better organize a chassis loaded with fiber modules. It allows for the routing of fibers through the brackets so that the tangling of the wires is greatly avoided.

The Fiber Manager increases the number of fibers that can be routed on a Total Access 5000 Chassis. It allows for the management of up to 176 fibers with 1.6 mm diameter to the left of the System Controller Module (SCM) and 176 fibers with 1.6 mm diameter to the right of the SCM.

The Fiber Manager mounts to the front and immediately below the Total Access 5000 Chassis, replacing the standard fiber tray. The Manager is shipped with a fan filter holder, mounting brackets, and mounting screws for installation.

Product Features

- Industry-leading 10 year warranty
- NEBS, Telcordia GR-63-CORE and Telcordia GR-1089-CORE Compliant
- Does not require routine hardware maintenance



Fiber Manager

ADTRAN, Inc.

901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963 8000
256 963 8030 fax

General Information

800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

888 5ADTRAN
support@adtran.com
www.adtran.com/support

Where to Buy

800 827 0807
www.adtran.com/where2buy

Post-Sales

Technical Support

800 726 8663
support@adtran.com
www.adtran.com/support

Regional Offices

Dallas, TX
972 830 9070
Denver, CO
303 471 9150
Kansas City, KS
800 471 8649
Newark, NJ
800 471 8656
Ontario, Canada
416 290 0585
Quebec, Canada
877 923 8726
San Antonio, TX
888 223 7671

International Inquiries

+1 256 963 8716
+1 256 963 6300 fax
international@adtran.com
www.adtran.com/global



TL19.1270



ADTRAN is an ISO 9001, ISO 14001,
and a TL 9000 certified supplier.

61187940G1-8A August 2011
Copyright © 2011 ADTRAN, Inc.
All rights reserved.

Total Access 5000 Fiber Manager

Product Specifications

Mechanical

- **Dimensions:** 1.75 in. H x 23.00 in. W x 11.00 in. D

Regulatory Standards

- NEBS Level 3
- GR-63-CORE
- GR-1089-CORE
- NRTL Listed
- FCC Part 15

Environmental

- **Operating Temperature:** -40°C to +65°C
- **Storage Temperature:** -40°C to +85°C
- **Relative Humidity:** Up to 95%, noncondensing

Ordering Information

Equipment	Part #
Total Access 5000 Fiber Manager	1187940G1

Specifications subject to change without notice. ADTRAN and Total Access are registered trademarks of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.