

ADTRAN

# FSU7101

## Multi-Gigabit Optical Services Platform



### Benefits

- **Simultaneously Supports 1G/10G Line Cards**
- **1G/10G ONU Coexistence on 10G PON**
- **160G Uplink Capacity**
- **DPoE 1.0 Qualified**
- **MEF 9 & 14 Certified**
- **Investment Protection**
  - Two 80Gbps Per PON Slot (for Redundancy)
  - 2.56Tbps Backplane Capacity
  - Redundant 100 Mbps Control Channels
  - Upgradeable Switching Modules
  - Dual Function Slot Design Supports Use of Multipurpose Line Cards
- **High Density**
  - 160 1G-EPON Interfaces
  - 128 10G-EPON Interfaces
- **High Throughput and Reliability**
  - 720 Gbps Switching Capacity Per Switch Card
  - 1.44 Tbps Switching Capacity Per System (Active/Active)
  - 160 Gbps Uplink (10 Gbps x 8 Ports x 2 Switch Cards)
  - L2/L3 Capable
  - Upgrade Path to Higher Switching and Uplink Capacities

### Overview

**The FSU7101 Optical Services Platform (OSP) supports the delivery of symmetrical multi-gigabit (1G/10G) Ethernet services.** It can be utilized as an integrated, modular or hybrid optical access platform.

It supports IEEE802.3ah/av standards compliant EPON/10G-EPON and Point-to-Point Ethernet (CWDM/DWDM) modules while supporting both DOCSIS (DPoE) and manual (CLI) provisioning methods.

When paired with the FCM7151 Ethernet Access Line Card (EALC) and FSR7142/43 Remote Optical Services Device (ROSD), it creates a modular access architecture that conserves fiber, increases PON reach beyond typical 20km, and increases density of the platform by four to eight times.



# ADTRAN FSU7101

---

## Product Specifications

### Chassis (FSU7101)

- Chassis: (FSU7101)
- Dimensions: 17.5" x 17.1" x 13.2"  
(444mm x 434mm x 334mm) (H X W X D)
- Weight: ~100lb (45kg)
- Height: 19-inch, 10RU (excluding air baffles)
- Mount: Flush or Middle
- Input Voltage: -42V DC to -57V DC
- Power Consumption: 3kW Max
- Operating Temperature: 32°F-104°F (0°C-40°C)
- Operating Humidity: 10 ~ 90% RH (non-condensing)
- Number of Line Card Slots: 16

### Switch Card (FSW7112)

- Remote Access: I/F RJ-45 10/100/1000BASE-T x 1 (auto negotiation)
- Serial Interface: RJ-45 (RS232C) x 1
- Uplink Interface: SFP/SFP+ (1000B/10GBASE-SR/LR) x 8
- Uplink Capacity: 160G (Active/Active)
- SD Card Slot: SDHC
- Number of Supported Line Cards: Maximum 16

### 1G Line Card (FCM7121)

- PON I/F: SFP x 10, 1000BASE-PX20E-D
- Wavelength: Upstream 1260 ~ 1360nm/Downstream 1480 ~ 1500nm
- Transmission Rate: 1.25Gbps
- Bandwidth Control: Dynamic Bandwidth Allocation
- Maximum Number of ONUs: 64 Per Port

### 10G Line Card (FCM7133)

- PON I/F: XFP x 8; 10GBASE-PR-D3, 10/1GBASE-PRX-D3, 1000BASE-PX30-D
- Wavelength: Upstream 1260 ~ 1280nm/Downstream 1575 ~ 1580nm
- Transmission Rate: 10.3 Gbps
- Bandwidth Control: Dynamic Bandwidth Allocation
- Maximum Number of ONUs: 128 Per Port

### Certificates

- EMI FCC Part15 Class A, ICES-003 Class A
- Safety UL/CSA 60950-1, IEC 60950-1 & 60825-1
- MEF 9 and 14
- DPoE 1.0 Qualified

# Multi-Gigabit Optical Services Platform

---

## Management

- SNMPv1/v2c/v3
- CLI (SSH/Telnet)
- TFTP/SFTP client
- Syslog
- SNTP client
- RADIUS/TACACS+ AAA client
- L2/L3/L4 based ACL
- Remote Firmware upgrade (OLT & ONU)
- Remote ONU Control

## Routing

- ECMP
- Static IPv4/6 Routing
- IPv4
  - ◆ IPv4/31 Bit Mask Interface Addressing
  - ◆ RIPv2, OSPFv2
- IPv6
  - ◆ M-ISIS
- DHCP Relay Agent (Option82)

## L2 Switching

- Link Aggregation (LAG) with LACP (802.3ad)
- DPoE 1.0 Compliant EPL Service with Provider Bridging (Q in Q)
- ELINE/ELAN

## QoS

- DBA of EPON (Hierarchical Weighted Round Robin)
- Eight Priority Queues for Each Line Card and Uplink Port
- Policing with Two Rate Triple Color Markers (trTCM)

## DPoE/EPON

- Maximum 64 ONUs Per PON with FCM7121 Line Card
  - ◆ Maximum 8 LLIDs Per ONU
- Maximum 128 ONUs Per PON with FCM7133 Line Card
  - ◆ Maximum 16 LLIDs Per ONU

## Security

- PON Encryption (AES128 CFB mode)
- ONU Authentication
- Secure Software Download (SSD) via DOCSIS

## Diagnostic

- Statistics counters
- Ping and Traceroute
- ONU Loopback
- Optical Monitoring
- Optical Shutdown

# ADTRAN FSU7101

## Ordering Information

Equipment	Part No.
ADTRAN FSU7101 Optical Services Platform	4757101FSUDCF1
Switch Card FSW7112	1757112FSWF2
1G Line Card FCM7121	1757121FCMF1
10G Line Card FCM7133	1757133FCMF1



**ADTRAN, Inc.**  
901 Explorer Boulevard  
Huntsville, AL 35806

**General Information**  
800 9ADTRAN  
256 963 8000  
[www.adtran.com/contactus](http://www.adtran.com/contactus)

**Canada—Montreal, Quebec**  
+1 877 923 8726  
+1 514 940 2888  
[sales.canada@adtran.com](mailto:sales.canada@adtran.com)

**Mexico and Central America**  
+1 52 55 5280 0265 Mexico  
[sales.cala@adtran.com](mailto:sales.cala@adtran.com)

### 64757101FSUDCF1-8B

April Copyright © 2019 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN® and the other trademarks listed at [www.adtran.com/trademarks](http://www.adtran.com/trademarks) are registered trademarks of ADTRAN, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit [www.adtran.com/warranty](http://www.adtran.com/warranty).

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of ADTRAN items (e.g. commodities, technology, software), please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense).

