

ADTRAN

# 6212-4

SDN Programmable XGS-PON Remote OLT



## Benefits

- Cuts headend space congestion, power consumption and fiber exhaust issues
- Supports Gigabit+ speeds and subscriber capacity via remote, non-blocking FTTH architecture
- Accelerates differentiated service creation via open, multi-vendor SDN programmability
- Up to 512 FTTH subscribers supported via 4 ports of 10G PON
- Purpose built to support gigabit broadband and SLA-based multi-gig business and backhaul services
- Supports low-latency services such as emerging augmented and virtual reality applications
- Aligned with Distributed Access Architectures (DAA) and Fiber Deep strategies (up to 80km)
- Robust outside plant design with strand mounting and environmentally sealed packaging
- Fully redundant power supplies and uplink connections

## Overview

**The ADTRAN SDX 6212-4 is an environmentally sealed, virtualized 10G XGS-PON Remote OLT.** Part of ADTRAN's portfolio of 4-port 10G PON devices, the SDX 6212-4 reduces time-to-market and subscriber connection costs by using Fibre to the Home (FTTH) and Distributed Access Architectures (DAA) to effectively deliver Gigabit and triple play services.

The next-generation SDX 6212-4 supports four XFP interfaces for 10/10G XGS-PON to support up to 128 users per PON (up to 512 subscribers across four PON ports). It offers four non-blocking 10G uplink interfaces, with embedded redundancy options, to ensure scalability to support next-generation residential, business and mobile backhaul/fronthaul services.

The ADTRAN family of remote and virtualized OLTs support modern SDN control protocols allowing MSOs to effectively execute their transition to virtualized, managed and orchestrated

SD-Access service architectures. In addition, SDX 6212-4 virtual R-OLT supports virtualization of Layer 3 processing and other functionality resulting in a simpler, greener, more cost-effective virtualized R-OLT architecture.

The ADTRAN SDX 6212-4 supports the Open Networking Forum (ONF) Trellis disaggregated, software-defined access (SD-Access) architecture that includes programmable elements, such as the ADTRAN SDX 8200 and 8300 series aggregation switches. From a programmability perspective, the SDX 6212-4 has open APIs that utilize standard NETCONF/YANG interfaces for all management functions, easing integration into an SDN environment.

The ADTRAN SDX 6212-4's environmentally hardened, clam-shell factor can withstand extreme weather conditions, while providing reliable broadband connectivity.



# ADTRAN 6212-4

---

## Product Specifications

### System Features

- 4x 10GE/1GE uplink SFP+ ports
- 4x 10G/10G XGS-PON XFP ports
- CWDM and DWDM uplink optics supported
- Full-duplex switching capacity: 80 Gbps
- **Management interfaces:** RS-232C, 10/100/1000BASE-T

### Mechanical

- 11 x 19.5 x 10 in. (279 x 495 x 254 mm) (W x L x H)
- **Maximum Weight:** 30 lbs (13.6 kg)

### Electrical Power Specification

- **Maximum power consumption:** 85W
- Standard CATV plant power, pseudo square wave, 45 - 95 VAC RMS at 60Hz

### Environmental

- **Operating Temperature:** -40°C to 65°C
- **Humidity:** 5 – 95%

### PON

- Wire-speed processing
- 10 Gbps/10 Gbps symmetric rate (downstream/upstream)
- 128-bit Advanced Encryption Standard (AES) encryption engine for PON security and privacy with up to 128 unique keys.
- Forward Error Correction (FEC) encoding and decoding
- Flexible optical transceiver interfaces for multiple vendor support
- Hardware-based configurable Dynamic Bandwidth Allocation (DBA)
- Supports local and remote loopback test, and MEF services

### Layer 2

- **MAC address:** up to 64K (shared) MAC management
- VLAN
  - ◆ Max 4 K VLANs, 802.1Q support
  - ◆ 802.1ad Q-in-Q
  - ◆ Tagging/stacking
  - ◆ Port to VLAN mapping
  - ◆ Service to VLAN mapping
- Link aggregation
  - ◆ 802.3ad link aggregation
  - ◆ Load-balancing based on source and destination MAC/IP

### Security

- Packet Filtering
  - ◆ DHCP filtering
  - ◆ Packet filtering with ACLs
  - ◆ EtherType VLAN ID

### Layer 3

- Multicast
  - ◆ IGMP v2/v3
  - ◆ IGMP snooping , IGMP join/leave, IGMP join filter/count limit
- DHCP
  - ◆ DHCP Relay, Blocks illegal IP users, DHCP option 82, DHCP Snooping

# SDN Programmable 10G PON Remote OLT

---

## Quality of Service

- **Layer 2:** source/destination MAC address, VLAN ID, COS field
- **Marking/remarking:** DSCP, 802.1p
- Packet drop
- Mirroring to port, redirect to port
- 8 queues per port
- SPQ, DWRR, hybrid (SPQ+DWRR)
- Egress rate shaping per port/queue with 1 Mbps unit
- IP anti-spoofing
- ARP packet traffic limit
- Blocking of user-to-user flows
- Subscriber isolation

## System Security

- **Access control:** RADIUS; TACACS+; DHCP, DHCP 82/60 options, and static IP
- CPU packet filtering with ACL
- CPU packet rate-limit

## Management

- Remote access
  - ◆ SSH, NETCONF
- OS/configuration
  - ◆ Remote OS upgrade using TFTP, FTP, SFTP
  - ◆ Dual flash image
  - ◆ Remote configuration data download

## Ordering Information

Equipment	Part No.
SDX 6212-4 SDN Programmable 10G PON	11971430F1

---



**ADTRAN, Inc.**  
901 Explorer Boulevard  
Huntsville, AL 35806

**General Information**  
+1 256 963 8000  
[www.adtran.com/contactus](http://www.adtran.com/contactus)

**Headquarters—EMEA**  
**ADTRAN GmbH**  
[sales.cewe@adtran.com](mailto:sales.cewe@adtran.com)

**South Europe**  
[sales.southeurope@adtran.com](mailto:sales.southeurope@adtran.com)

**Middle East and Africa**  
[sales.mea@adtran.com](mailto:sales.mea@adtran.com)

**Australia/New Zealand**  
[sales.australia@adtran.com](mailto:sales.australia@adtran.com)

**I61119971430F1-8A**

**February** Copyright © 2019 ADTRAN, Inc. All rights reserved. ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN® and the other trademarks listed at [www.adtran.com/trademarks](http://www.adtran.com/trademarks) are registered trademarks of ADTRAN, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

ADTRAN warranty duration and entitlements vary by product and geography. For specific warranty information, visit [www.adtran.com/warranty](http://www.adtran.com/warranty).

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of ADTRAN items (e.g. commodities, technology, software), please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense).

**ADTRAN**  
Certified  
Supplier



ISO 9001  
ISO 14001  
TL 9000

**TL9000**  
TL10 1270